





Automated Hematology Analyzer
MEK-6500J/K
MEK-6510J/K

A reliable partner in your laboratory

exible

■ User-friendly compact design

Based on over 40-year experience in manufacturing hematology analyzers, Nihon Kohden's Celltac α provides stress-free operation with newly designed hardware and software interface.

■ Flexible aspiration modes

Celltac α has several blood aspiration modes. The cap pierce mode (available on MEK-6500J/K Series) contributes to safer operation by eliminating the chance of touching blood. Capillary mode enables 10µL capillary blood. Sampling from neonate or infant earlobe, heel.

Large data capacity

Celltac α uses SD cards for reliable data storage. Over 15,000 results can be stored. Reliable



Specifications

Parameters	WBC, LY%, MO%, GR%, LY, MO, GR, RBC, HGB, HCT, MCV, MCH, MCHC, RDW-CV, RDW-SD, PLT, PCT, MPV, PDW
Measurement methods	WBC, RBC, PLT – impedance method HCT – calculation from histogram HGB – cyanmethemoglobin optical detection WBC differential – calculation from histogram
Measurement modes	Open Closed Pre-dilution WBC high WBC low Capillary
Counting time	60 sec/sample (Open mode)
Sample volume aspirated	30 μL (CBC) for normal measurement mode 10 or 20 μL for pre-dilution mode, 10 μL for capillary mode
Data storage	Over 15,000 results including histograms can be stored on an SD card.
LCD display	5.7 inch 240 × 320 dots TFT-LCD
Dimensions	230 W × 450 D × 428 H (mm)
Weight	Approx. 20 kg

Reagents, Controls, Calibrator



Hematology control

MEK-3DN (normal) T455 MEK-3DL (low) MEK-3DH (high) (2mL)



Hemolyzing reagent for CBC

HEMOLYNAC-3N Cyanide-free

Detergent CLEANAC



Calibrator

MEK-CAL T457 (2mL)

Diluent

ISOTONAC⋅3

Detergent (Bleach) CLEANAC-3





SD card

QM-001D Y154D QM-002D Y154E

Up to 15,000 results can be stored

Consumable



Micro capillary adaptor YZ-0373A T810B

Over 40 Years of Experience with In Vitro Diagnostic



لاب ماركت



